TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION

IMPORTANT:
THIS DRAWING SHALL BE USED IN
COMBINATION WITH THE GENERAL
NOTES MD 104.00-01 - MD 104.00-18 AND
STANDARD DETAILS MD 104.01-01 MD 104.01-81

NOTES:

DRUMS SHALL BE USED IN THE MERGING TAPER.

DRUMS. 36" CONES OR TALL WEIGHTED CONES * SHALL BE USED ADJACENT TO THE WORK AREA.

PROTECTION VEHICLE WITH FLASHING LIGHTS
SHALL BE USED TO PROTECT THE WORK AREA.
PER SECTION 10.4 OF THE GENERAL NOTES.
PLACEMENT OF THE PROTECTION VEHICLE SHALL
BE AS SHOWN IN THIS FIGURE. WHILE ALLOWING FOR
THE ROLL AHEAD DISTANCE ANTICIPATED WITH IMPACTS.

REFER TO GENERAL NOTE 7.8 FOR GUIDANCE ON USING CHANNELIZING DEVICES TO DELINEATE THE EDGE OF THE ROADWAY.

* TALL WEIGHTED CONES - CONES 42" TALL WITH A NARROW, WEIGHTED BASE, SEE STANDARD SPECIFICATION 104.14.

THIS TYPICAL APPLICATION DOES NOT APPLY TO PAVING OPERATIONS, BUT CAN BE USED AT THE DISCRETION OF THE ENGINEER.

KEY:

CHANNELIZING

⇧

DIRECTION OF TRAFFIC



WORK AREA


ARROW PANEL



TRUCK OR TRAILER-TRUCK MOUNTED ATTENUATOR APPROVED VEHICLE

洪

APPROVED VEHICLE SAFETY LIGHT



** DRUMS SHALL BE USED IN THE MERGING TAPER
DRUMS, 36" CONES OR TALL WEIGHTED CONES
SHALL BE USED IN THE WORK AREA

APPROVED

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

APPROVAL • SHA APPROVAL • FEDERAL

APPROVAL • APPROVAL • FEDERAL **BEVISIONS** HIGHWAY ADMINISTRATION 7-27-09 7-1-09 APPROVAL APPROVAL REVISED 8-11-10 REVISED 7-29-10 StateHighway REVISED 8-20-14 REVISED 8-11-14

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

CHANNELIZATION DEVICE SPACING GREATER THAN 40 MPH

STANDARD NO.

MD 104.01-30 C